

WATERPROOFING A BASEMENT

PRODUCTS YOU'LL NEED



Hypastat

Available in 5L and 20L containers
Hypastat is a DG product.

[SHOP NOW](#)



Strata100

Available in 4L, 8L or 20L containers.
Comes in Grey or White.

[SHOP NOW](#)

APPLICATION

✓ Spray on **Hypastat** using a hand sprayer with a coarse wetting nozzle, and leave on for at least 30 mins.

Coverage:

- Mix at a ratio of 1:2 with water. i.e. 20L **Hypastat** is mixed with 40L water, so will make 60L. Coverage 240m².
- Once mixed this will cover approx. 4 sq metres per litre.

✓ Rinse off with a water blaster and ensure you have a clean, dry surface before continuing.

✓ Mix the **Strata-100** sealer in equal quantities of Part A & Part B and thoroughly mix together until mix is consistent. 1:1 ratio (Part A and Part B)

✓ Apply 1 layer of the **Strata-100** mix using a brush or roller.

Coverage:

- Approximate coverage is 5-8 square metres per litre per coat.
- Apply at outside temperature 8°C - 20°C.
- Do not apply when rain or dew is forecast.

✓ Leave it to dry for 2-4 hours (20°C) or more.

To download the **SDS & Data Sheets** for these products please visit www.stratacote.co.nz/sds-and-data-sheets/

The information above is the best available to Stratacote Ltd and its affiliated companies relating to our products and the use of our products. It is based on tests believed to be reliable. Stratacote Ltd assumes no liability for any damages incurred in association with the use of the Hypastat or Strata100. Information is subject to change without notice.